



since 1895

PVC Primer

PRODUCT DESCRIPTION

PVC Primer is a single-component polyurethane primer with excellent adhesion to both plasticised and unplasticised PVC. The PVC Primer is used in conjunction with Garland's roof coating systems such as White-Knight when being applied over plastisol or PVC coated steel sheeting. PVC Primer contains no toluene.

PRODUCT ADVANTAGES

Quick Curing - PVC Primer cures quickly, allowing the installing contractor to proceed with the coating works the same day.

Easy To Apply - The primer has the consistency of a thin clear liquid which is easily applied using roller or brush.

Promotes Adhesion - PVC primer has been specifically developed to promote adhesion between PVC or plastisol coated steel and polyurethane coatings.

APPLICATION

The surface must be clean, dry and free from chalking dirt, grease, oil residues and any other contamination. The substrate must be of suitable quality to receive the system. Substrates should be cleaned thoroughly by power washing and allowed to dry prior to priming.

Plastisol and PVC substrates give the best results if solvent wiped immediately prior to use.

Apply by brush or roller ensuring a uniform coverage of the substrate is achieved. Product should be over coated once cured and tack free, typically after 15 minutes @ 20 °C but within the coating window 12 hours.

LIMITATIONS

Surfaces must be thoroughly dry prior to application.

Temperature should be between 5 °C and 30 °C.

Do not apply the primer if rainfall is expected within the curing period.

Technical Data	Reactivation Primer
Viscosity	600 cps
Typical Solids by weight	15%
Colour	Clear
Drying Time to touch @ 20°C	10 minutes
Shelf Life	12 Months
Coverage	0.25 l/m ²
Packaging	5 l pail

For specific application recommendations, please contact your regional Garland Technical Manager or the Garland Technical Department.

For more information visit us at www.garlandukltd.co.uk



since 1895

The Garland Company UK Limited

Glevum Works, Upton Street
Gloucester, United Kingdom GL1 4LA
Phone: 01452 330646
Fax: 01452 330657
info@garlandukltd.co.uk

Tests verified by independent laboratories. Actual roof performance specifications will vary depending on test speed and temperature. Data reflects samples randomly collected. A ± 10% variation may be experienced. The above data supersedes all previously published information. Consult your Garland Regional Technical Manager or the Garland Technical Department for more information.

© 2014 The Garland Company UK Limited

PVC 0914