



Dura-Walk[®] Cleaner

PRODUCT INFORMATION

DESCRIPTION

Dura-Walk Cleaner is a clear, colourless liquid based on methyl methacrylate (MMA).

USAGE

Dura-Walk Cleaner is an excellent agent for the cleaning of application tools.

PACKAGING

5 kg and 10 kg metal pails

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS (LIQUID STATE)

Density at 20°C:	0.94 g/cm ³	ISO 2811
Viscosity at 20°C:	< 1 mPa * s	DIN 53018
Flash point:	+ 11.5°C	ISO 1516

USAGE GUIDELINES

Dura-Walk Cleaner can be reused several times. It must be stored and transported in well closed original containers. If it is heavily soiled with remainders of resin and catalyst, Dura-Walk Cleaner may form a deposit or flakes, whose volume is increased by storage at high temperatures. In such cases Dura-Walk Cleaner must be disposed of and replaced by fresh material. Dura-Walk Cleaner must be disposed of as solid matter. To achieve this, add 10% of Dura-Walk Cleaner to any uncured and remaining resins and leave to cure.

STORAGE

Store in a cool dry place and in original packaging. Optimal storage temperature is between 15 - 20°C.

HEALTH AND SAFETY PRECAUTIONS

Please refer to the Safety Data Sheets for the products used.