



since 1895

SAFETY DATA SHEET

PVC Primer

Page: 1

Compilation date: 27/07/2011

Revision date: 25/06/2013

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PVC Primer

REACH registered number(s): 01-2119457290-43,01-2119471330-49,

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: The Garland Company UK Ltd

Unit 5 Glevum Works

Upton Street

Gloucester

Gloucestershire

GL1 4LA

UK

Tel: 01452 330646

Fax: 01452 330657

Email: info@garlandukltd.co.uk

1.4. Emergency telephone number

Emergency tel: 01452 330646

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36; -: R66; -: R67

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 2: H225

Most important adverse effects: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 2



Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.
Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.

Label elements under CHIP:

Hazard symbols: Highly flammable.
Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S3/9/49: Keep only in the original container in a cool, well-ventilated place.
S46: If swallowed, seek medical advice immediately and show this container or label.
S33: Take precautionary measures against static discharges.
S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour.
S60: This material and its container must be disposed of as hazardous waste.

Precautionary phrases: Very high VOC content 50% or above

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 3

Hazardous ingredients:

ETHYL METHYL KETONE - REACH registered number(s): 01-2119457290-43

EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	---------	---------------------------------	--	--------

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---------------------------------	--	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 5

Hazardous ingredients:

ETHYL METHYL KETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m ³	899 mg/m ³	-	-

ACETONE

UK	1210 mg/m ³	3620 mg/m ³	-	-
----	------------------------	------------------------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

Hand protection: Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves. for low exposure use nitrile gloves. The user has a legal duty to carry out a COSHH risk assessment to determine the correct glove.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: 56

upper: 13

Autoflammability°C: 460

Flammability limits %: lower: 1.8

Flash point°C: -19

Relative density: 0.86

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
VAPOURS	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	>2000	mg/kg
DERMAL	RBT	LD50	>2000	mg/kg

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
-----	-----	------	------	-------

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 7

ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	LC50	100	mg/l
ALGAE	LC50	100	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Wet waste: Arrange for disposal by a licenced waste disposal company

Disposal of packaging: Arrange for disposal by a licenced waste disposal company

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 8

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This product is classified as a mixture. CLP classification for information only.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

[cont...]

SAFETY DATA SHEET

PVC Primer

Page: 9

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.