



Dura-Walk[®] Thinner

PRODUCT INFORMATION

DESCRIPTION

Dura-Walk Thinner is a milky cloudy, colourless liquid based on methyl methacrylate (MMA).

USAGE

Dura-Walk Thinner is used as a reactive diluent for primers and sealers of the Dura-Walk Balcony Systems. If required, it is added to the Dura-Walk primer or sealer in a maximum proportion of 10% by weight of resin. The use of Dura-Walk Thinner does not cause any loss in the cure or quality of the Dura-Walk primers and sealers; it only reduces the viscosity of the resin.

PACKAGING

5 kg and 10 kg metal pails

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS (LIQUID STATE)

Density at 20°C:	0.94 g/cm ³	ISO 2811
Viscosity at 20°C:	< 1 mPa * s	DIN 53018
Flash point:	+ 11.5°C	ISO 1516

USAGE GUIDELINES

Mix the Dura-Walk Thinner with the primer or sealer resins up to a maximum of 10% by weight until the desired viscosity is achieved. Then add the appropriate amount of Dura-Walk Catalyst depending on ambient and substrate temperature.

STORAGE

Store in a cool dry place and in original packaging. Optimal storage temperature is between 15 - 20°C.

HEALTH AND SAFETY PRECAUTIONS

Please refer to the Safety Data Sheets for the products used.